



New smart investment for your business

E Entry IP Lineup
Easy Installation & Operation
Economic Value
Series

HD Weatherproof Dome Network Camera

1.3 Megapixel 720p Weatherproof Dome Network Camera Equipped with IR LED



K-EF134L Series
K-EF134L02AE
(Focal Length 2.8 mm)



Key Features

- High-performance CMOS image sensor.
- Focal length : 2.8 mm
- H.264 & MJPEG dual-stream encoding
- 30fps@1.3 M (1280 × 960) & 30fps@720p (1280 × 720).
- Support ICR for day time and night time operation.
- Max. IR LEDs length 30 m.
- IP66 rated water and dust resistant.
- PoE.

HD Weatherproof Network Camera

1.3 Megapixel 720p Weatherproof Network Camera Equipped with IR LED



K-EW114L Series
K-EW114L03AE
(Focal Length 3.6 mm)



Key Features

- High-performance CMOS image sensor.
- Focal length : 3.6 mm
- H.264 & MJPEG dual-stream encoding
- 30fps@1.3 M (1280 × 960) & 30fps@720p (1280 × 720).
- Support ICR for day time and night time operation.
- Max. IR LEDs length 30 m.
- IP66 rated water and dust resistant.
- PoE.

Network Disk Recorder

4 ch 4 PoE (K-NL304K) Network Video Recorder



K-NL304K

Key Features

- Up to 4 channel with 1080p realtime live view
- H.264 / MJPEG dual codec decoding
- 4 PoE ports
- HDMI / VGA simultaneous video output



Specifications

K-EF134L02AE

K-EW114L03AE

Camera		
Image Sensor	Approx. 1/3 type CMOS image sensor	Approx. 1/3 type CMOS image sensor
Min Illumination	0.1 lx / F1.2 (color)*1, 0 lx (IR on)	0.1 lx / F1.2 (color)*1, 0 lx (IR on)
Gain	Auto/Manual	Auto/Manual
Back light compensation	OFF/ BLC/ HLC/ WDR	OFF/ BLC/ HLC/ WDR
Shutter speed	Auto/ Manual, 1/3 sec~1/100000 sec	Auto/ Manual, 1/3 sec~1/100000 sec
Day / Night	Auto(ICR) / Color/ Black & White	Auto(ICR) / Color/ Black & White
IR LED Light	Irradiation distance: 30 m	Irradiation distance: 30 m
White Balance	Auto/ Sunny/ Night/ Outdoor/ Manual	Auto/ Sunny/ Night/ Outdoor/ Manual
Digital Noise Reduction	3DNR ON/ OFF	3DNR ON/ OFF
Privacy masking	Up to 4 areas	Up to 4 areas
Video Motion Detection	On/ Off	On/ Off
Lens		
Focal Length	2.8 mm	3.6 mm
Angular Field of View	H: 89° V: 64°	H: 71° V: 55°
Network		
Network	10BASE-T/ 100BASE-TX, RJ45 connector	10BASE-T/ 100BASE-TX, RJ45 connector
Resolution	1.3 M (1280x960) / 720P (1280x720)/ D1 (704x576/704x480) / CIF (352x288/352x240)	1.3 M (1280x960) / 720P (1280x720)/ D1 (704x576/704x480) / CIF (352x288/352x240)
Image compression method	H.264/ H.264H/ H.264B/ MJPEG	H.264/ H.264H/ H.264B/ MJPEG
Frame Rate	1 to 25/30 fps	1 to 25/30 fps
Protocol	IPv4/ IPv6, HTTP, HTTPS, SSL, TCP/ IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, DDNS, FTP, QoS, Bonjour, ONVIF compatible	IPv4/ IPv6, HTTP, HTTPS, SSL, TCP/ IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, DDNS, FTP, QoS, Bonjour, ONVIF compatible
Maximum concurrent access number	20 users (Number of sessions that can connect to cameras at the same time)	20 users (Number of sessions that can connect to cameras at the same time)
General		
Power source	12 V DC, PoE (IEEE802.3af compliant)	12 V DC, PoE (IEEE802.3af compliant)
Power Consumption	12 V DC: 320 mA / Approx. 3.8 W PoE 48 V DC: 80 mA / Approx. 3.8 W (Class 0 device)	12 V DC: 400 mA / Approx. 4.8 W PoE 48 V DC: 100 mA / Approx. 4.8 W (Class 0 device)
Ambient Operating Temperature / Humidity	-30 °C to +60 °C {-22 °F to 140 °F} 10 % to 90 % (no condensation)	-30 °C to +60 °C {-22 °F to 140 °F} 10 % to 90 % (no condensation)
Water and Dust Resistance	Main body: IP66	Main body: IP66
Dimensions	Φ108 mm × 85 mm (H) {ø4-1/4 inches × 3-11/32 inches (H)}	Φ70 mm × 165 mm (H) {ø2-3/4 inches × 6-1/2 inches (H)}
Weight (approx.)	Approx. 250 g {0.55 lbs}	Approx. 380 g {0.84 lbs}

*1 [Image Adjust] Shutter: (0-)80 ms, Gain: (0-)50"

Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.
- Panasonic cannot be responsible for the performance of the network and/or other manufacturers' products used on the network.

- All pictures are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.



信興集團 信興科技有限公司

九龍尖東麼地道67號半島中心B座9樓 www.panasonic.oa.hk

查詢熱線 2313 0666

保養及維修
信興電器服務中心有限公司
電話：2406 5777

DISTRIBUTED BY:

