

Panasonic
BUSINESS

Document Scanner
KV-S7097
KV-S7077

Improve Your Work Efficiency with Dual Scanning



High-Speed Scanning

95 ppm / 190 ipm (KV-S7097)
75 ppm / 150 ipm (KV-S7077)

* A4/Letter, Landscape, 300 dpi, Binary/Colour



- ✓ ADF / Flatbed Scanning
- ✓ Single Touch Scanning
- ✓ Multi-Crop
- ✓ Double-Feed Skip

ADF/Flatbed Scanning

Scanning is possible from the ADF or flatbed, depending on the document.

ADF

- 200 Sheets
- Duplex Scanning



Flatbed

- Books
- Thin Papers



Multi-Crop

Place various sized documents on the flatbed and scan them all at once, then crop whatever parts you need.



Scan all together.



Crop each one.

Single Touch Scanning

Easy scanning with a single press of the button.


* Previously set jobs must be registered from the PC to the scanner.
Up to 9 job settings can be registered.



Select the registered scan settings from the display.



Press the button.



Scanning is easy, even when settings are complicated.

Double-Feed Skip

Cancels double-feed errors to continue scanning.



The scanner pauses for labels or envelopes.



Press the skip button.



Scanning starts again.

Hardware Image Processing (ADF Only)

Drops in the scanning speed can be minimised by using hardware for frequently used image processing.

Specifications

| | |
|----------------------------|--|
| Scanning Face | Duplex & Flatbed |
| Scanning Method | ADF: 3-line colour hybrid CIS (Front and back sides), Flatbed: 3-line colour hybrid CIS |
| Scanning Resolution*1 | 100 dpi - 600 dpi (1 dpi step) and 1,200 dpi (software) (Optical 600 dpi) |
| Scanning Speed*2 | KV-S7077 ADF: Landscape / A4 or Letter, Simplex: 95 ppm, Duplex: 190 ipm Flatbed: 0.7 sec. (Letter / Portrait), 0.8 sec. (A4 / Portrait) KV-S7077 ADF: Landscape / A4 or Letter, Simplex: 75 ppm, Duplex: 150 ipm Flatbed: 0.8 sec. (Letter / Portrait), 0.8 sec. (A4 / Portrait) |
| Double-Feed Detection | Ultrasonic (The length of documents that can be detected is 70 mm or more.) |
| Image Compression | MH, MMR (Software ICP), JPEG |
| Binary Mode Halftone | Dither, Error Diffusion |
| Document Size | ADF Manual feeding: 48 x 70 mm (1.9 x 2.75 in.) to 302 mm x No Limited (11.9 in. x No Limited) Automatic feeding: 48 x 70 mm (1.9 x 2.75 in.) to 302 x 432 mm (11.9 x 17 in.) Flatbed Maximum size: 297 x 432 mm (11.7 x 17 in.) |
| Document Weight | 31 - 127 g/m ² (8.3 - 34 lbs.)*, Smaller than A7 size: 127 g/m ² (34 lbs.) only |
| Feed Tray Capacity | 200 sheets: 80 g/m ² (21lbs.) |
| Supported Operating System | Windows® XP SP3 (32 bit/64 bit), Windows Vista® SP2 (32 bit/64 bit), Windows® 7 (32 bit/64 bit), Windows 8 (32 bit/64 bit), Windows 8.1 (32 bit/64 bit), Windows 10 (32 bit/64 bit), Windows Server® 2003 SP2 (32 bit/64 bit), Windows Server® 2008 SP2 (32 bit/64 bit), Windows Server® 2008 R2 SP1 (64 bit), Windows Server® 2012 (64 bit) |

*1 When scanning a document larger than A5 size at high resolutions over 600 dpi, the scanning may fail due to insufficient memory. *2 The scanning speed differs depending on the host computer, the operating system, the application, the measuring method, the quantity of data in the image, and the paper type. The scanning speed depends on a measuring method of Panasonic. *3 Use "Thin Paper Feeding Mode" when scanning the document less than 40 g/m² (10.6 lb.). For details about "Thin Paper Feeding Mode", refer to the Image Capture Plus, TWAIN, or ISIS help.

*4 About the environmental conditions of Imprinter Unit (KV-SS014), refer to the "Information" leaflet of the optional imprinter unit. When printing in conditions outside of the imprinter unit's operating environment, the printing result may be faded or printing may not occur.



As an ENERGY STAR® partner, Panasonic has determined that this product meets the ENERGY STAR guidelines for energy efficiency.



Digital Imprinter

The "Digital imprinter" enables additional printing to the scanned image data.

| | |
|---------------------------------|---|
| Interface | USB 3.0 / USB 2.0 interface |
| External Dimensions (W X D X H) | 755 x 508 x 289 mm (29.7 x 20.0 x 11.4 in.) |
| Weight | 29.0 kg (64 lbs.), 30.0 kg (66 lbs.) include accessories |
| Power Requirement | AC 100-127 V, 50/60 Hz, 1.5 A AC 100-240 V, 50/60 Hz, 1.5-0.8 A AC 220-240 V, 50/60 Hz, 0.8 A |
| Power Consumption | Maximum (Scanning) 90 W: 1.5 A (100-127 V), 90 W: 0.8 A (220-240 V) Minimum (Ready) 38 W (100-127 V / 220-240 V) Sleep 1.4 W or less (100-127 V / 220-240 V) Power Off 0.3 W or less (100-127 V / 220-240 V) |
| Operating Environment ** | Temperature: 5 °C to 35 °C (41 °F to 95 °F) Humidity: 20 % RH to 80 % RH (No dewdrop) |
| Storage Environment ** | Temperature: -10 °C to 50 °C (14 °F to 122 °F) Humidity: 8 % RH to 75 % RH (No dewdrop) |
| Accessories | CD-ROM: Device driver, ISIS driver software, TWAIN driver software, User utility, Scan Button Setting Tool, Image Capture Plus with OCR Engine, Operating Manual, Control data sheet (PDF) Quick Installation Guide, Power Cord, USB Cable (USB 3.0), Shading paper, Hopper tray |
| Options | Roller exchange kit: KV-SS015, Roller cleaning paper: KV-SS03, Imprinter Unit (Pre): KV-SS014, Ink cartridge: KV-SS021 |

Trademarks and registered trademarks

- ENERGY STAR and the ENERGY STAR mark are registered U.S. marks.
- ISIS is a registered trademark or trademark of EMC Corporation in the United States and other countries.
- Windows, Windows Vista and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- All other brand or product names are the property of their respective holders.

This product is designed to reduce hazardous chemical substances in accordance with the RoHS directive.

* The power requirement differs depending on the country/area.

- All photographs in this brochure are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

DISTRIBUTED BY :

Panasonic

Document Scanner: <http://panasonic.net/pcc/products/scanner/>

Printed in Japan MG-SCNL029EN 1606NSP/ZZZ-U2